

Stryker Glide™

Lateral Air Transfer System

Medical

Rental Solutions Delivered by



1 800 STRYKER Option 3

Universal | Hospital | Services®

Laterally transfer patients with ease

Air technology lets patients ride on a cushion of air

Safety straps secure patients to the transfer mat

Complete system conveniently stores in roller tote

Thermal protection for patient safety



BackSmart™ Patient Transfer System

The Stryker Glide allows two nurses to laterally transfer a patient safely while reducing the potential for back injury. The core of the system is an inflatable mat that lifts and floats the patient on a cushion of air, so that with very little effort, caregivers can transfer even very large patients from one surface to another.



Patient Transfer



Blower Unit



Roller Tote

Stryker Glide™

Lateral Air Transfer System

stryker®



Medical

3800 E. Centre Ave.
Portage, MI 49002
t: 269 329 2100 f: 269 329 2311
toll free: 800 787 9537

www.stryker.com

System Standard Features

- Durable Stryker Glide transfer mat with protective cover
- Lightweight blower unit with expandable air hose (10 ft max.)
- Convenient roller tote
- Foldable transfer bridge
- Hook and strap to hang blower unit

Stryker Glide Specifications

	Regular	Large	Bariatric
• Model Number	3061-000-028	3061-000-032	3061-000-046
• Mat Only	3061-500-028	3061-500-032	3061-500-046
• Overall Width	28" (71 cm)	32" (81 cm)	46" (117 cm)
• Overall Length	78" (198 cm)	78" (198 cm)	78" (198 cm)
• Weight Capacity	500 lbs (226 kg)	700 lbs (272 kg)	1000 lbs (453 kg)
• Transfer Mat Material	Nylon, urethane undercoated, thermal insulation, water resistant, non-latex		

*Stryker reserves the right to change specifications without notice.
System is manufactured exclusively for Stryker Medical.*

Protective Cover Specifications

	Regular	Large	Bariatric
• Model Number	3061-120-028	3061-120-032	3061-120-046
• Overall Width	45" (114 cm)	49" (124 cm)	57" (145 cm)
• Overall Length	79" (201 cm)	79" (201 cm)	79" (201 cm)

Blower Unit Information

• Model Number	3060-400-000
• Approvals	c-us UL
• Electrical Classification	Class II
• EMC	IEC 60601-1-2
• Voltage	120 VAC
• Power Wattage	1,440 W
• Ampere Rating	12A
• Frequency	50/60 Hz
• Blower Unit Weight	8.5 lb (3.9 kg)

Warranty

- One-year limited warranty
- Stryker will repair (or replace) this system if defective in material or workmanship
- Does not include cleaning, damage caused by accident, neglect, misuse, improper installation or operation, any damage caused from unauthorized repairs, maintenance, modifications or tampering by anyone other than a Stryker representative

Optional Features

- Expandable air hose (25 ft max.)
- All system components can also be purchased separately



Mixed Sources
Product group from well-managed
forests, controlled sources and
recycled wood or fibre
Cert no. SW-COC-1530
www.fsc.org
© 1996 Forest Stewardship Council

Copyright © 2007 Stryker
PC/SCG-7.5M-0508, 07-SMD-2027
Mkt Lit-155-111406 Rev C